

# 6500 SERIES



## Clean Room Granulators

### COMPACT DESIGN. MAXIMUM PERFORMANCE.

Sterling's clean room granulator is the answer for high quality regrind in sprue, runner, and small part applications. Good Manufacturing Process (GMP) and medical molding require the elimination of dust in the manufacturing environment. Our 6500 Series Clean Room granulator is designed to meet clean room standards. The dual pneumatic flap in-feed and dust enclosure prevent dust and particles from escaping the granulator.



#### Features

- Special dual flap in-feed ensures complete containment of dust and particles
- Clam shell dust enclosure provides quick and easy, no tools access
- 3 blade open rotor with rotary side walls
- Solid dowel and bolted construction
- Locking swivel casters mounted on base provides mobility
- 5 hp TEFC motor (230 volts or 460 volts / 3 phase / 60 Hz)
- Control voltage wired with electrical / mechanical safety interlock (115 volts / 1 phase / 60 Hz)

#### Options

- No options available

# 6500 SERIES

## Clean Room Granulators

Model	6512CR	6516CR
Standard Configuration		
Machine Size (WxLxH), in. (mm)	26 x 30 x 62 (660 x 762 x 1575)	28.5 x 27.5 x 51.2 (724 x 699 x 1300)
Rotor Type	3-blade open with rotating end discs	
Rotor/Cutting Circle Dia., in. (mm)	6.3 (160)	6.3 (160)
Rotor Speed, rpm	210	210
Rotor Knives	3 steep angle	
Bed Knives	2	
Cutting Chamber Opening (HxW), in. (mm)	6.5 x 12 (165 x 305)	6.5 x 16 (165 x 406)
Feed Height, in. (mm)	64 (1626)	64 (1626)
Controls, volts (3 phase/60Hz) <sup>1</sup>	NEMA 12 control enclosure 230 or 460	
Drive Motor HP - Rotor, hp (kW)	5 (3.7)	
Drive parts - Rotor	V-belts	
Infeed	Top feed dual pneumatic flaps	
Screen Size, in (mm)	1 piece reversible screen	
Choice of 1/4, 5/16, 3/8, 1/2, or 5/8		
Estimated Throughput, lbs/hr (kg/hr)	150 (68)	200 (91)
Discharge Type	Vacuum bin with 1.5" or 2" vacuum probe	
Weight, lbs (kg)	1050 (476)	1130 (513)

<sup>1</sup> Machine is equipped with electrically operated solenoid for dual flaps on hopper (24V or 120V). Customer is responsible for all signals and control equipment to operate and cycle the solenoids / pneumatic flaps.

