



## ENVIRONMENTALLY FRIENDLY PORTABLE CHILLING



Sterling's GP Series offers 20-50 kW (5-15 tons of refrigeration) for their air-and-water-cooled portable chillers and provides a leaving coolant temperature range of 20°F to 80°F (-7.5°C to 30°C). Offering the smallest footprint in the industry, the GP Series is also the first product line to utilize environmentally friendly R410a refrigerant.

### Features

- Environmentally friendly, R410a refrigerant
- Branch motor circuit protection
- "Y" strainer in process water line to evaporator
- Off-the-shelf modular controller is accurate to within  $\pm 1^\circ\text{F}$  ( $\pm 0.6^\circ\text{C}$ )
- Easy-to-read LCD display showing system operating status, Set Point, and To-Process temperature; remote mount without special configuration
- Multiple-line screen, 20 character x 8 line display
- Stamped, stainless steel, horizontally mounted pump assures reliability
- Leaving water temperature range of 20°F to 80°F (-7.5°C to 30°C)
- Non-ferrous piping
- Air-cooled units feature aluminum fin tube condensers with easy on/off, washable air filters
- Water-cooled units equipped with water regulating valves with tube-in-tube condensers
- No tools necessary to access the mechanical cabinet
- 4" swivel casters with locks
- Electronic hot gas bypass valve
- Non-fused disconnect switch with single point power connection
- 1 year compressor and labor warranty; 2 year parts warranty; 3 year limited controller warranty
- NEMA 12 electrical enclosure

## PORTABLE CHILLERS



# GP SERIES



| Model              | 20                                      | 30          | 40          | 50          |           |
|--------------------|---|-------------|-------------|-------------|-----------|
| Compressor         | Hermetic scroll with compressor staging |             |             |             |           |
| Compressor HP (kW) | 5 (3.7)                                 | 7.5 (5.6)   | 10 (7.5)    | 15 (11)     |           |
| Evaporator         | Stainless steel brazed plate            |             |             |             |           |
| Reservoir gal (L)  | 20 (76)                                 |             | 40 (151)    |             |           |
| Pump HP (kW)       | 1.5 (1.1)                               | 2 (1.5)     |             | 3 (2.2)     |           |
| Height in (mm)     | GPAC                                    | 63 (1600)   | 81.5 (2070) | 80.5 (2515) | 99 (2515) |
|                    | GPWC                                    | 60.5 (1537) |             |             | 79 (2007) |
|                    | GPRC                                    |             |             |             |           |
| Depth, in (mm.)    | 35 (889)                                |             | 44 (1118)   |             |           |
| Width, in (mm.)    | 35 (889)                                |             |             |             |           |
| Weight lbs (kg)    | GPAC                                    | 520 (235)   | 700 (320)   | 760 (345)   | 950 (430) |
|                    | GPWC                                    |             |             |             |           |
|                    | GPRC                                    | 550 (250)   | 730 (335)   | 790 (360)   | 980 (445) |

Contact factory for detailed information on remote condensers.




The magnetic connection on the controller interface allows it to be mounted anywhere on the unit. This allows the chiller to be placed anywhere on the process line since there is no front or back to the unit.



Scroll Compressor



Evaporator



Locking swivel casters



Air-cooled condenser



## ENVIRONMENTALLY FRIENDLY PORTABLE CHILLING



Sterling's GP Series offers 70-210 kW (20-60 tons of refrigeration) for their air-and-water-cooled portable chillers and provides a leaving coolant temperature range of 20°F to 80°F (-7.5°C to 30°C). Offering the smallest footprint in the industry, the GP Series is also the first product line to utilize environmentally friendly R410a refrigerant.

### Features

- Environmentally friendly, R410a refrigerant
- Branch motor circuit protection
- "Y" strainer in process water line to evaporator
- Off-the-shelf modular controller is accurate to within +/-1°F (+/-0.6°C)
- Easy-to-read LCD display showing system operating status, Set Point, and To-Process temperature; remote mount without special configuration
- Multiple-line screen, 20 character x 8 line display
- Stamped, stainless steel, horizontally mounted pump assures reliability
- Leaving water temperature range of 20°F to 80°F (-7.5°C to 30°C)
- Non-ferrous piping
- Compressor staging tandems
- Air-cooled units feature aluminum fin tube condensers with easy on/off, washable air filters
- Variable speed fans standard
- Water-cooled units equipped with water regulating valves with shell-and-tube condensers
- No tools necessary to access the mechanical cabinet
- 4" swivel casters with locks for 70-105 models; mounting channel for 140-210 models
- Electronic hot gas bypass valve
- Non-fused disconnect switch with single point power connection
- 1 year compressor and labor warranty; 2 year parts warranty; 3 year limited controller warranty
- NEMA 12 electrical enclosure

## PORTABLE CHILLERS



# GP SERIES



| Model                     |             | 70                                      | 90         | 105        | 140         | 175         | 210         |  |
|---------------------------|-------------|---|------------|------------|-------------|-------------|-------------|--|
| <b>Compressor</b>         |             | Hermetic scroll with compressor staging |            |            |             |             |             |  |
| <b>Compressor HP (kW)</b> |             | 20 (15)                                 | 25 (18.7)  | 30 (22.4)  | 40 (30.0)   | 50 (37.3)   | 60 (45.0)   |  |
| <b>Evaporator</b>         |             | Stainless steel brazed plate            |            |            |             |             |             |  |
| <b>Reservoir</b>          |             | 70 (265)                                |            |            | 140 (530)   |             |             |  |
| <b>Pump HP (kW)</b>       |             | 5 (3.7)                                 |            |            |             |             |             |  |
| <b>Height (in, mm)</b>    | <b>GPAC</b> | 82 (2083)                               |            | 100 (2540) |             |             |             |  |
|                           | <b>GPWC</b> | 79 (2007)                               |            |            |             |             |             |  |
|                           | <b>GPRC</b> |   |            |            |             |             |             |  |
| <b>Depth (in, mm.)</b>    | <b>GPAC</b> |   |            |            | 105 (2667)  |             | 140 (3556)  |  |
|                           | <b>GPWC</b> | 70 (1778)                               |            |            |             |             |             |  |
|                           | <b>GPRC</b> |   |            |            | 105 (2667)  |             |             |  |
| <b>Width(in, mm.)</b>     |             | 44 (1118)                               |            |            |             |             |             |  |
| <b>Weight lbs (kg)</b>    | <b>GPAC</b> | 1420 (645)                              | 1520 (690) | 1900 (864) | 2280 (1035) | 2850 (1295) | 3800 (1725) |  |
|                           | <b>GPWC</b> | 1410 (640)                              | 1510 (686) | 1880 (855) | 2210 (1005) | 2790 (1268) | 3630 (1650) |  |
|                           | <b>GPRC</b> | 1420 (645)                              | 1520 (690) | 1900 (864) | 2280 (1035) | 2850 (1295) | 3800 (1725) |  |

Contact factory for detailed information on remote condensers.

The magnetic connection on the controller interface allows it to be mounted anywhere on the unit. This allows the chiller to be placed anywhere on the process line since there is no front or back to the unit.



Scroll Compressor



Evaporator



Locking swivel casters



Air-cooled condenser



**Sterling New Berlin**  
 2900 S 160th Street  
 New Berlin, WI 53151 USA  
 Tel: +1 262 641 8610  
 Fax: +1 262 641 8653  
 www.sterlco.com

**Sterling Schaumburg**  
 1100 E Woodfield Rd #550  
 Schaumburg, IL 60173 USA  
 Tel: +1 847 273 7700  
 Fax: +1 847 273 7804

**Sterling Warsaw**  
 ul.Dziakowa 115  
 02-234 Warszawa  
 Tel: +48 22 390 9720  
 Fax: +48 22 390 9724

**Sterling India**  
 Gat No. 191/1, Sandbhor Complex,  
 Mhalunge, Chakan, Tal Khed,  
 Dist. Pune 410501, India  
 Tel: +91 21 35329112  
 Fax: +91 20 40147576

**Sterling Suzhou**  
 109 Xingpu Road SIP  
 Suzhou, China 215126  
 Tel: +86 512 8717 1919  
 Fax: +86 512 8717 1916

