

HARMO HRXf SERIES



HRX-300SWf and
HRX-300GWf

SUPERIOR PERFORMANCE AND SMART PROGRAMMING

With pinpoint accuracy and repeatability, rugged durability, and high speed performance, the HRXf Series Full Servo Extraction Robots are redefining the automation industry. These powerful yet very cost effective robots are perfect for automating horizontal molding machines from 40–80 tons in both three and five axis configurations.

The HRXf Series features the highest quality linear guides on all axes, employing THK rail and bearing systems. The redesigned kick frame provides more rigidity for enhanced support and repeatability.



Features

- All axis AC digital servo actuation-absolute encoder
- Three-dimensional axis movement
- Thick-walled aluminum extrusion traverse beam with steel sub-weldment
- THK linear guide rail with large block bearings (all axes)
- C-Axis 90° wrist flip
- Programmable part extraction from stationary or moving platen
- One (1) part vacuum circuit with detection
- One (1) mechanical circuit with detection
- One (1) sprue grip circuit with detection
- SPI-ready with 32 pin DIN plug

Options

- Two-stage telescopic vertical arm construction for low overhead environment (standard on HRX-300 and larger robots)
- A-Axis pneumatic two-position 0-90 or 0-180 degree wrist rotation
- Additional pressure and/or vacuum circuit(s)
- Machine platen spacer with custom mounting bolt hole pattern
- EOAT quick-change system (robot & EOAT side)
- Extended stroke lengths (varies by model)
- End of beam support
- EuroMap 12 or 67 IMM interface (SPI interface/plug is standard)
- SPI interface plug kit (10 amp/32 pin) for molding machine side
- Transformer for voltages other than 200-220 VAC/three phase

HARMO HRXf SERIES

HRX-300SWf and
HRX-300GWf

SPECIFICATIONS

Model	Vertical Stroke (mm)		Stripe Stroke (mm)		Traverse Stroke (mm)	Max. Payload (kg)	Machine Weight (kg)
	Main	Sub	Main	Sub			
HRX-300SWf	1100	-	1015	-	1800 (2000)	10 (Including EOAT)	355
HRX-800GWf		1150	861	861			380

Model	Working Air Pressure (mpa)	Air Consumption (Nℓ/Cyc) *1	Drive System	Control Method	Power Supply (V)	Power Consumption (W)
HRX-300SWf	0.6	2.7	Digital AC Servo Motor (3/5 Axis)	PTP•CP	3P 200 ACV +10%/-15% (50Hz/60Hz)	1700
HRX-300GWf		2.9				2300

*1 Additional 63Nℓ/min is consumed for each vacuum ejector

DIMENSIONS (MM)

