



DIGITAL DOSING SYSTEM

PRECISION FEEDING FOR EXTRUSION OR INJECTION MOLDING

The SDD Digital Dosing System offers precise feeding for almost any plastics machine, whether your application is injection molding, blow molding, or extrusion. The SDD 2 dosing unit offers the ability to use dual additives or regrind at different rates.

The SDD dosing unit uses a variable speed DC drive motor and a correctly sized dosing disc to precisely feed powder or pellet additives, at the set rate, into the throat of the processing machine. Precision design and closed loop control ensures high accuracy to setpoint.

Material changeover has never been easier. Just lift two quick disconnects and remove the additive station. With the optional spare station, changeover is immediate. The simple changeover design reduces downtime and safety risk.

Features

- Disc style feeder module to dose pellets, micro batch, granulate or powders (please specify)
- 0-12 RPM variable speed, closed loop drive
- Choice of several styles and sizes of discs for precise additive feeding
- Clear plastic additive hopper with fill cover
- Quick disconnect additive hopper for "off the machine" clean-out/material change
- Sampling tube for simple calibration
- 2" diameter material feed tube with 6" square mounting flanges (top and bottom)

Options

- Disc style feeder module to dose pellets, microbatch, granulate or powders
- Spare hopper assembly for immediate changeover
- Optional motor speeds (6 RPM, 36 RPM)
- Optional hopper capacities
- Audible alarm
- Alarm light
- Low level sensors
- Hopper loaders for automatic refill
- Virgin supply hoppers
- Larger base (3" or 4")





The S150 Controller is designed for either injection molding applications or extrusion applications. Both controllers are microprocessor-based, and the feeder's motor speed is monitored continuously to compensate for fluctuations in the screw speed of the processing machine. The controllers are easy to operate, with user-friendly icons and storage of up to 10 recipes. Additive consumption is conveniently displayed on the 5 digit LED display.


Control Features

Available for either extrusion or injection molding machines, the controller automatically calculates calibration values and allows for direct input of desired percentages. The controller features user-friendly icons and a 5 digit LED display that shows additive consumption. It stores up to 10 recipes, with memory backup for recipe and data storage.

- Dry contact signal input (injection) and dry contact alarm output
- Extruder tracking capability
- Input for level probe for both virgin material and additives
- IP64 shielding
- Short circuit proof outputs
- Operates between 32 to 122°F (0 to 50°C)
- Operating voltage 115 VAC +/-10%, 50/60 Hz or 220/1/50-60 Hz
- Connected load of 100 W maximum during operation
- Thermal device protection



SDD 1
 Feed Rate: 0.2-800 lbs/hr
 Operating Load: 0.2 kW
 Weight: 51lbs (23kg)



SDD 2
 Feed Rate: 0.2-800 lbs/hr
 Operating Load: 0.4 kW
 Weight: 100lbs (45kg)



Sterling New Berlin
 2900 S 160th Street
 New Berlin, WI 53151 USA
 Tel: +1 262 641 8610
 Fax: +1 262 641 8653
 www.sterlco.com

Sterling Schaumburg
 1100 E Woodfield Rd #550
 Schaumburg, IL 60173 USA
 Tel: +1 847 273 7700
 Fax: +1 847 273 7804

Sterling Warsaw
 ul.Dziakowa 115
 02-234 Warszawa
 Tel: +48 22 390 9720
 Fax: +48 22 390 9724

Sterling India
 Gat No. 191/1, Sandbhor Complex,
 Mhalunge, Chakan, Tal Khed,
 Dist. Pune 410501, India
 Tel: +91 21 35329112
 Fax: +91 20 40147576

Sterling Suzhou
 109 Xingpu Road SIP
 Suzhou, China 215126
 Tel: +86 512 8717 1919
 Fax: +86 512 8717 1916

